

Rec'd PCT/STC 20 AUG 2004
PCT/IB 03 / 00582

14.02.03



Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

REC'D 12 MAR 2003

WIPO

PCT

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-
gen stimmen mit der
ursprünglich eingereichten
Fassung der auf dem näch-
sten Blatt bezeichneten
europäischen Patentanmel-
dung überein.

The attached documents
are exact copies of the
European patent application
described on the following
page, as originally filed.

Les documents fixés à
cette attestation sont
conformes à la version
initialement déposée de
la demande de brevet
européen spécifiée à la
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

02075717.5

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk

DEN HAAG, DEN
THE HAGUE,
LA HAYE, LE

09/12/02

BEST AVAILABLE COPY



Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

**Blatt 2 der Bescheinigung
Sheet 2 of the certificate
Page 2 de l'attestation**

Anmeldung Nr.:
Application no.:
Demande n°: 02075717.5

Anmeldetag:
Date of filing:
Date de dépôt: 22/02/02

Anmelder:
Applicant(s):
Demandeur(s):
Lumileds Lighting Netherlands B.V.
5684 PJ Best
NETHERLANDS

Bezeichnung der Erfindung:
Title of the invention:
Titre de l'invention:
Compact lighting system and display device

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s) revendiquée(s)

Staat:
State:
Pays:

Tag:
Date:
Date:

Aktenzeichen:
File no.
Numéro de dépôt:

Internationale Patentklassifikation:
International Patent classification:
Classification internationale des brevets:

/

Am Anmeldetag benannte Vertragsstaaten:
Contracting states designated at date of filing:
Etats contractants désignés lors du dépôt:

AT/BE/CH/CY/DE/DK/ES/FI/FR/GB/GR/IE/IT/LI/LU/MC/NL/PT/SE/TR

Bemerkungen:
Remarks:
Remarques:



P.B.5818 - Patentlaan 2
2280 HV Rijswijk (ZH)
☎ +31 70 340 2040
TX 31651 epo nl
FAX +31 70 340 3018

Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

Generaldirektion 1

Directorate General 1

Direction Générale 1

Dusseldorp, Jan Charles
INTERNATIONAAL OCTROOIBUREAU B.V.,
Prof. Holstlaan 6
5656 AA Eindhoven
NL

Datum/Date

09/12/02

Zeichen/Ref./Réf.

PHNL020135EP-P

Anmeldung Nr./Application No./Demande n°/Patent Nr./Patent No./Brevet n°.

02075717.5 2423

Anmelder/Applicant/Demandeur/Patentinhaber/Proprietor/Titulaire

Lumileds Lighting Netherlands B.V.

Übersendung von/Transmission of/Envoi de

Antrag vom/Request dated/Requête du 02/12/02

- ☐ Kopien bei Akteneinsicht nach Regel 94(3) EPÜ
Copies in the case of inspection of files pursuant to Rule 94(3) EPC
Copies en cas d'inspection publique selon la règle 94(3) CBE
- ☐ Beglaubigung
Certification
Certification
- ☒ 2 Prioritätsbeleg(e)/priority document(s)/document(s) de priorité R. 94(4)
- ☐ — Ausfertigung(en) der Patenturkunde nach Regel 54(2) EPÜ
Duplicate of the patent certificate pursuant to Rule 54(2) EPC
Duplicata du certificat de brevet, selon la Règle 54(2) CBE
- ☐ Auszug aus dem Register nach Regel 92(3) EPÜ
Extract from the register pursuant to Rule 92(3) EPC
Extrait du registre selon la Règle 92(3) CBE
- ☐ Auskunft aus den Akten nach Regel 95 EPÜ
Communication of information contained in the files pursuant to Rule 95 EPC
Communication d'informations contenues dans le dossier selon la Règle 95 CBE
- ☐ Akteneinsicht nach Regel 94(2) EPÜ
Inspection of files pursuant to Rule 94(2) EPC
Inspection publique selon la Règle 94(2) CBE

Rechnung folgt/Invoice to follow/Facture suivra

unter Zugrundelegung von
on the basis of the following
sur la base suivante

Verwaltungsgebühr/Administration fee/Taxe d'administration

☒

Kosten für Kopien/Cost of copies/Frais pour copies (_____)

Blätter)
pages)
feuilles)

☐

Telefax

☐

☒

Zur Abbuchung vom laufenden Konto
to be debited from the deposit account
à débiter du compte courant

Nr.
No. 28090021
n°

PERON L (TEL: 3632)



P.B.5818 - Patentlaan 2
2280 HV Rijswijk (ZH)
☎ +31 70 340 2040
TX 31651 epo nl
FAX +31 70 340 3016

Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

Generaldirektion 1

Directorate General 1

Direction Générale 1

Dusseldorp, Jan Charles
INTERNATIONAAL OCTROOIBUREAU B.V.,
Prof. Holstlaan 6
5656 AA Eindhoven
NL

Datum/Date

09/12/02

Zeichen/Ref./Réf.

PHNLO20135EP-P

Anmeldung Nr./Application No./Demande n°/Patent Nr./Patent No./Brevet n°.

02075717.5 2423

Anmelder/Applicant/Demandeur/Patentinhaber/Proprietor/Titulaire

Lumileds Lighting Netherlands B.V.

Übersendung von/Transmission of/Envoi de

Antrag vom/Request dated/Requête du 02/12/02

- ☐ Kopien bei Akteneinsicht nach Regel 94(3) EPÜ
Copies in the case of inspection of files pursuant to Rule 94(3) EPC
Copies en cas d'inspection publique selon la règle 94(3) CBE
- ☐ Beglaubigung
Certification
Certification
- ☒ 2 Prioritätsbeleg(e)/priority document(s)/document(s) de priorité R. 94(4)
- ☐ Ausfertigung(en) der Patenturkunde nach Regel 54(2) EPÜ
Duplicate of the patent certificate pursuant to Rule 54(2) EPC
Duplicata du certificat de brevet, selon la Règle 54(2) CBE
- ☐ Auszug aus dem Register nach Regel 92(3) EPÜ
Extract from the register pursuant to Rule 92(3) EPC
Extrait du registre selon la Règle 92(3) CBE
- ☐ Auskunft aus den Akten nach Regel 95 EPÜ
Communication of information contained in the files pursuant to Rule 95 EPC
Communication d'informations contenues dans le dossier selon la Règle 95 CBE
- ☐ Akteneinsicht nach Regel 94(2) EPÜ
Inspection of files pursuant to Rule 94(2) EPC
Inspection publique selon la Règle 94(2) CBE

Rechnung folgt/Invoice to follow/Facture suivra

unter Zugrundelegung von
on the basis of the following
sur la base suivante

Verwaltungsgebühr/Administration fee/Taxe d'administration

☒

Kosten für Kopien/Cost of copies/Frais pour copies (_____)

Blätter)
pages)
feuilles)

☐

Telefax

☐

☒

Zur Abbuchung vom laufenden Konto
to be debited from the deposit account
à débiter du compte courant

Nr.
No. 28090021
n°

PERON L (TEL:3632)

Auskunftsstelle/Information office/Service d'information

Compact lighting system and display device

The invention relates to a lighting system provided with a light-emitting panel comprising

a front wall, a rear wall situated opposite thereto,

at least one light source comprising a light-emitting diode provided with a

5 translucent lens-shaped cover,

at least one light in-coupling structure for coupling light from the light source into the light-emitting panel,

while, during operation, light originating from the light source is incident on the light in-coupling structure and distributes itself in the light-emitting panel.

10 The invention also relates to a display device provided with said lighting system.

Such lighting systems are known per se and are also denoted edge lighting systems. They are used inter alia as backlighting systems in (picture) display devices, for example for TV sets and monitors. Such lighting systems are particularly suitable for use as
15 backlights for non-emissive displays such as liquid crystal display devices, also denoted LCD panels, which are used in (portable) computers or (portable) telephones.

Said display devices usually comprise a substrate provided with a regular pattern of pixels which are each controlled by at least one electrode. The display device utilizes a control circuit for achieving a picture or a data graphical display in a relevant field
20 of a (picture) screen of the (picture) display device. The light originating from the backlight in an LCD device is modulated by means of a switch or modulator, various types of liquid crystal effects being used. In addition, the display may be based on electrophoretic or electromechanical effects.

Such lighting systems are also used as luminaires for general lighting purposes
25 or for shop lighting, for example shop window lighting or lighting of (transparent or semi-transparent) plates of glass or of (transparent) plates of glass or of (transparent) synthetic resin on which items, for example jewelry, are displayed. Such lighting systems are further used as window panes, for example for causing a glass wall to radiate light under certain conditions, or to reduce or block out the view through the window by means of light. A

further alternative application is the use of such lighting systems for illuminating advertising boards.

In the lighting systems mentioned in the opening paragraph, the light source used is usually comprises a plurality of optoelectronic elements, also referred to as electro-optical elements, for example electroluminescent elements, for example light-emitting diodes (LEDs). These light sources are usually provided in the vicinity of or tangent to a light-transmitting edge surface of the light-emitting panel, in which case light originating from the light source is incident on the light-transmitting edge surface during operation and distributes itself in the panel.

A lighting system for illuminating an LCD panel is known from US-A 5,921,652. The light source used is formed by light-emitting diodes (LEDs) which couple light into a light-emitting panel, also denoted light pipe, via a so-called light transition area. The light is mixed in said light transition area.

A lighting system of the above type has the lighting system occupies too much space. ---

It is an object of the invention to eliminate the above disadvantage wholly or partly. According to the invention, a lighting system of the kind mentioned in the opening paragraph is for this purpose characterized in that

in that the light in-coupling structure is conically or frusta-conically shaped towards the light source, and

in that the thickness d_p of the light-emitting panel is smaller than the diameter d_c of the translucent lens-shaped cover of the light source.

By increasing the area of the light in-coupling structure the efficiency of the in-coupling of light from the light source into the light-emitting panel is increased. A light source based on a light-emitting diode, normally, comprises a light-emitting part (a chip) covered by a translucent lens-shaped cover. The dimensions of this lens-shaped cover as well as the shape of the light in-coupling structure largely determine how (efficient) light is transferred from the light source to the light-emitting panel.

In the known lighting system, the light in-coupling structure in the known light system is an edge surface, normally a side wall of the light-emitting panel. Said edge surface

is provided between the front wall and the rear wall of the light-emitting panel. To obtain a sufficient efficiency of the in-coupling of light originating from the light source into the light-emitting panel of the known lighting panel with edge surfaces, the thickness of the light-emitting panel has to be larger than the characteristic dimension of the translucent lens-shaped cover, for example the diameter d_c of the translucent lens-shaped cover.

The tapering shape of the light in-coupling structure which gradually becomes narrower in the direction of the light source according to the invention provides a relatively high efficiency of the in-coupling of light from the light source into the light-emitting panel. Not wishing to be held to any particular theory, there exists an inverse relationship between the thickness of the light-emitting panel and the efficiency of the in-coupling of light from the light source into the light-emitting panel. Due to the relatively large effective surface of the light in-coupling structure, the dimensions of the light-emitting panel can be reduced while retaining a relatively high efficiency of the in-coupling of light into the light-emitting panel. A compact lighting system is obtained through the measure according to the invention.

Preferably, the light in-coupling structure is of a prismatic or pyramidal shape. Light in-coupling structures in the form of a prism or a pyramid are particularly useful in attaining a high specific surface of the light in-coupling structure. The point (or the frusta-conical end) of the pyramid is preferably directed towards the (geometrical) center of the translucent lens-shaped cover and is preferably (approximately) in contact with the translucent lens-shaped cover.

In a preferred embodiment of the lighting system according to the invention the light in-coupling structure forms an integral part of the light-emitting panel. Preferably, the light-emitting panel and the light in-coupling structure of the lighting system are molded in one piece.

A preferred embodiment of the lighting system according to the invention is characterized in that light-guidance means are provided in the vicinity of the light source and the light-emitting panel encompassing the light in-coupling structure, said light-guidance means guiding the light originating from the light source towards the light in-coupling structure.

Preferably, the (inner) surface of the light-guidance means (9) facing the light in-coupling structure (4) is reflecting or is provided with a reflecting material. The light-guidance means function as a (specular) mirror guiding the light originating from the light source towards the light in-coupling structure.

Preferably, the light-guidance means are elliptically shaped. Elliptically shaped mirrors efficiently guide the light originating from the light source towards the light in-coupling structure. In an alternative embodiment the light-guidance means (9) are faceted. Faceting renders it possible to direct the light in specific directions during reflection.

5 The light source used may be formed by one or more light-emitting diodes (LEDs) and/or by LEDs of different colors which are combined with one another. Colors may be mixed in a desired manner through a suitable use of LEDs, for example for making white light of a desired color temperature. Preferably, the light source comprises three light-emitting diodes. The LEDs preferably comprise the combinations of red, green, and blue
10 LEDs known per se, or, for example, combinations of red, green, blue, and amber LEDs. LEDs with three light emission wavelengths may also be realized by means of two LEDs with different light emission wavelengths, wherein the LEDs of one of the types are (partly) provided with a phosphor, such that the light emission of the LED is converted by the phosphor into light of a third, desired light emission wavelength. A combination, known per
15 se, of the red, green, and blue LEDs renders it possible to realize color changes independently of the status of the display device. The use of LEDs has the further advantage that dynamic lighting possibilities are obtained. For this purpose, a sensor present at one of the edge surfaces measures the optical properties of the light emitted by the light source during operation.

20 The quantity of light emitted by the LEDs is adjusted in that the luminous fluxes of the light-emitting diodes are varied. This control of the luminous flux usually takes place in an energy-efficient manner. Thus the LEDs can be dimmed without an appreciable loss in efficacy. Preferably, the intensity of the light emitted by the light-emitting diodes is variable in response to the illumination level of a picture to be displayed by the display
25 device or in response to the level of the ambient light. Preferably, the color point of a picture displayed by the display device is determined by the lighting system. An (improved) dynamic range (for example contrast) of the picture to be displayed by the display device is achieved thereby.

 Preferably, each of the light-emitting diodes has a luminous flux of at least
30 10 lm. LEDs with such a high output are also denoted LED power packages. The use of these high-efficiency, high-output LEDs has the specific advantage that the number of LEDs required for a desired, comparatively high light output can be comparatively small. This benefits the compact construction and the efficiency of the lighting system to be manufactured. Further advantages of the use of LEDs are a comparatively very long useful

life, the comparatively low energy cost, and the low maintenance cost for a lighting system with LEDs.

5 The invention will now be explained in more detail with reference to a number of embodiments and a drawing, in which:

Fig. 1 is a cross-sectional view of a display device comprising an embodiment of the lighting system according to the invention, and

10 Fig. 2 shows the efficiency of the light in-coupling of various light in-coupling structures and various types of light-guidance means as a function of the thickness of the light-emitting panel.

The Figures are purely diagrammatic and not drawn true to scale. Some dimensions are particularly strongly exaggerated for reasons of clarity. Equivalent components have been given the same reference numerals as much as possible in the Figures.

15

Figure 1 is a cross-sectional view of a display device comprising an embodiment of the lighting system according to the invention. The lighting system comprises a light-emitting panel 1 of a light-transmitting material. The panel 1 is manufactured, for
20 example, from a synthetic resin, from acryl, from polycarbonate, from pmma, for example Perspex, or from glass. Light is transported through the light-emitting panel 1 during operation, utilizing total internal reflection (TIR). The light-emitting panel has a front wall 2 and a rear wall 3 opposite thereto. In Figure 1 at least one light source 6 is provided comprising a light-emitting diode 7 with a translucent lens-shaped cover 8. The lighting
25 system comprises at least one light in-coupling structure 4 for coupling light from the light source 6 into the light-emitting panel 1. During operation, light originating from the light source 6 is incident on the light in-coupling structure 4 and distributes itself in the light-emitting panel 1. According to the invention, the light in-coupling structure 4 is conically or frusta-conically shaped towards the light source 6.

30 By increasing the area of the light in-coupling structure 4 the efficiency of the in-coupling of light from the light source 6 into the light-emitting panel 1 is increased. The light in-coupling structure 4 gradually becomes narrower in the direction of the light source provides a relatively high efficiency of the in-coupling of light from the light source 6 into the light-emitting panel 1. Due to the relatively large effective surface of the light in-coupling

structure 4, the dimensions of the light-emitting panel 1 are reduced. According to the invention, the thickness d_p of the light-emitting panel 1 is smaller than the diameter d_c of the translucent lens-shaped cover 8 of the light source 6 (see Figure 1). A compact lighting system is obtained through the measure according to the invention.

5 In Figure 1 the light in-coupling structure 4 is shown separated from the light-emitting panel 1. In an alternative embodiment of the lighting system, the light in-coupling structure forms a integrated part of the light-emitting panel.

The light-emitting panel 1 emits light in the direction of the display device during operation, for example a liquid crystal display (LCD) device 12. The assembly of the
10 light source 6, the light-emitting panel 1, and the LCD device 12, whether or not accommodated in a housing (not shown in Figure 1), forms a display device for displaying, for example, (video) images.

The light-emitting panel 1 may further be provided with a sensor (not shown in Figure 1) for measuring the optical properties of the light. This sensor is coupled to control
15 electronics (not shown in Figure 1) for suitably adapting the luminous flux of the light source 6. A feedback mechanism can be realized by means of the sensor and the control electronics for influencing the quality and quantity of the light coupled out from the light-emitting panel 1.

Figure 2 shows the efficiency of the light in-coupling of various light in-
20 coupling structures and various types of light-guidance means as a function of the thickness d_p of the light-emitting panel. The efficiency is indicated by measuring the flux F of the light in the light-emitting panel 1 relative to (in Figure 2 as a percentage) the light emitter by the light source 6. The diameter d_c of the translucent lens-shaped cover 8 of the LED light source for the measurements in Figure 2 is 5.5 mm. The triangles in Figure 2 correspond to
25 measurements employing a light-emitting panel wherein the light in-coupling structure is a flat edge surface and for a light-guidance means with flat surfaces. It can be seen from Figure 2 (triangles) that the thickness of the thickness d_p of the light-emitting panel has to be relatively large, typically equal to or larger than the diameter d_c of the translucent lens-shaped cover of the LED light source, to obtain a flux efficiency higher than 80%. The squares in
30 Figure 2 correspond to measurements employing a light-emitting panel wherein the light in-coupling structure is a flat edge surface and for a light-guidance means with elliptical surfaces for a light-guidance means with a flat shape. It can be seen from Figure 2 (squares) that the situation is improved due to the elliptically-curved surfaces of the light-guidance means. In this situation the thickness of the thickness d_p of the light-emitting panel has to be

relatively large to obtain a flux efficiency higher than 80%. The circles in Figure 2 correspond to measurements for a lighting system according to an embodiment of the invention, employing a light-emitting panel 1 wherein the light in-coupling structure 4 has a prismatic shape pointing towards the translucent lens-shaped cover 8 and for a light-guidance means 9 with elliptical surfaces (see Figure 1). It can be seen from Figure 2 (circles) that a relatively high flux efficiency (approximately 80%) is obtained for a thickness d_p of the light-emitting panel which is approximately half of the diameter d_c of the translucent lens-shaped cover of the LED light source. A compact lighting system is obtained through the measure according to the invention.

10 It will be obvious that many modifications are possible to those skilled in the art within the scope of the invention.

The scope of protection of the invention is not limited to the embodiments given. The invention resides in each novel characteristic and each combination of characteristics. Reference numerals in the claims do not limit the scope of protection thereof.

15 The use of the verb "comprise" and its declinations does not exclude the presence of elements other than those specified in the claims. The use of the indefinite article "a" or "an" preceding an element does not exclude the presence of a plurality of such elements.

CLAIMS:

EPO - DG 1

22.02.2002

(38)

1. A lighting system provided with a light-emitting panel (1) comprising a front wall (2), a rear wall (3) situated opposite thereto, at least one light source (6) comprising a light-emitting diode (7) provided with a translucent lens-shaped cover (8),
5 at least one light in-coupling structure (4) for coupling light from the light source (6) into the light-emitting panel (1), while, during operation, light originating from the light source (6) is incident on the light in-coupling structure (4) and distributes itself in the light-emitting panel (1), characterized
10 in that the light in-coupling structure (4) is conically or frusta-conically shaped towards the light source (6), and in that the thickness d_p of the light-emitting panel (1) is smaller than the diameter d_c of the translucent lens-shaped cover (8) of the light source (6).
- 15 2. A lighting system as claimed in claim 1, characterized in that the light in-coupling structure (4) is of a prismatic or pyramidal shape.
3. A lighting system as claimed in claim 1 or 2, characterized in that the light in-coupling structure (4) is an integral part of the light-emitting panel (1).
20
4. A lighting system as claimed in claim 1 or 2, characterized in that light-guidance means (9) are provided in the vicinity of the light source (6) and the light-emitting panel (1) encompassing the light in-coupling structure (4), said light-guidance means (9) guiding the light originating from the light source (6) towards the light in-coupling structure
25 (4).
5. A lighting system as claimed in claim 4, characterized in that a surface of the light-guidance means (9) facing the light in-coupling structure (4) is reflecting or is provided with a reflecting material.

6. A lighting system as claimed in claim 4 or 5, characterized in that the light-guidance means (9) are elliptically shaped.

5 7. A lighting system as claimed in claim 4 or 5, characterized in that the light-guidance means (9) are faceted.

8. A lighting system as claimed in claim 1 or 2, characterized in that the light-emitting diode (7) has a luminous flux of at least 10 lm.

10

9. A display device provided with a lighting system as claimed in claim 1 or 2.

10. A display device as claimed in claim 9, which display device comprises a liquid crystal display (12).

ABSTRACT:


EPO - DG 1

22.02.2002

(38)

A compact backlight system for illuminating a display device (12) has a front wall (2) and a rear wall (3) situated opposite thereto. At least one light source (6) comprising a light-emitting diode (7) is provided with a translucent lens-shaped cover (8). The system has at least one light in-coupling structure (4) for coupling light from the light source (6) into the light-emitting panel (1). During operation, light originating from the light source (6) is incident on the light in-coupling structure (4) and distributes itself in the light-emitting panel (1). According to the invention the light in-coupling structure (4) is conically or frustaconically shaped towards the light source (6). The thickness d_p of the light-emitting panel (1) is smaller than the diameter d_c of the translucent lens-shaped cover (8) of the light source (6). Preferably, the light in-coupling structure (4) is of a prismatic or pyramidal shape.

Fig. 1



EPO - DG 1
22.02.2002
(38)

FIG. 1




FIG. 2

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: _____**

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.